

KN-S45F

4MP H.265 PTZ Wi-Fi Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



KN-S45F delivers 4MP live monitoring with a choice of 3.6mm lens option, With 4MP QHD live monitoring and 0~355° pan & 0~90°tilt features, KN-S45F ensures every corner of your home completely covered. It supports four night vision modes for clear-as day clarity even in pitch dark. With IP66 certified, the camera can be used outdoors under different weather conditions. With built-in spotlight and 110dB security siren, KN-S45F actively keeps unwelcome visitors away from what you care about.



H.265 4MP QHD
See more than 1080P



Human Detection
Quickly find human targets in you home



Smart Color Night Vision
Support four-mode night vision for clear-as day clarity even in pitch dark



Active Deterrence
Scare away unwelcome visitors with built-in spotlight and 110dB security siren



IP66
Weatherproof from dust and water



Two-way Talk
Real-time communicate with people at the camera



Diversified Storage
Supports NVR, Cloud Storage or Micro SD card (up to 256GB)



Alarm Notification
Sends instant motion-activated alerts to your mobile phone



Wi-Fi Connection
IEEE802.11b/g/n(2.4GHz)



Smart Tracking
Automatically tracks moving objects

Specifications

Camera

1/2.7"4 Megapixel Progressive CMOS
4MP (2560 x 1440)
Night Vision: 30m(98ft) Distance
3.6mm Fixed Lens
Field of View: 3.6mm: 88°(H), 46°(V), 107°(D)

Video & Audio

Video Compression: H.265/H.264
Up to 25/30 fps Frame Rate
16x Digital Zoom
Built-in Mic & Speaker, 110dB Siren
Two-way Audio

Notice Management

Motion Detection
Configurable Region
Human Detection

Network

1 x 100Mbps Ethernet Port
Wi-Fi:IEEE802.11b/g/n, Dual Antenna 120m Open Field
KBONE App: iOS, Android
ONVIF

Auxiliary Interface

Micro SD Card Slot (up to 256GB)
Built-in Mic & Speaker
Reset Button

General

DC 12V1A Power Supply
Power Consumption:<5.32W
Material: Plastic
Working Environment: -30°C~+60°C, Less Than 95%RH
IP66
Dimensions: 138.4 x 121.7x 257.5mm (5.45x 4.79 x 10.14 inch)
Weight: 565g (1.25lb)