

KX-F9412TN5

Edge Storage



- Embedded design for Linux and processing.
- 12 channel HD IP camera input, 4 channel analog camera input.
- Support image combining.
- 4 SATA ports for 3.5 and 2.5 inch HDD.
- Heat dissipation without mechanical fan, working environment -30 °C ~+70 °C .
- Support video and snapshot synchronization.
- Support LCD screen, VGA and HDMI port

Technical Specification

Technical Data

System resource	12 channel HD IP camera input(including pictures and video) 4 channel analog camera input
	Max 64Mbps incoming bandwidth, 64Mbps forward bandwidth
OS	Embedded Linux
UI	WEB or VGA/HDMI display
Video input	12 channel IP compression HD video input, 4 channel analog camera input.
Alarm input	4 channel
Alarm output	4 channel, relay output
Audio input	1 channel
Audio output	1 channel
Disk port	Max 4 SATA interface.
LCD screen	Display time, device information
eSATA port	1
RS232 serial port	2,One of them is used for debugging serial data
USB port	2
Display port	1 VGA,1 HDMI
Ethernet port	8 RJ45 10M/100M

Power,Size,Environment

Power supply	DC 12V
Power consumption	Max. 40W(with heater, HDD)
Working Temperature	-30 °C ~+70 °C
Working humidity	10% ~ 90%

Dimensions (mm/inch)

